

Your coconut fiber baling solution

Specially designed to effectively compact loose coconut fiber, palm fiber, flax fiber, abaca fiber, hem fiber, wool, cotton and other nature fiber materials into dense bales. An ideal choice for fiber processing industry to save more on storage space and transportation cost. Choose from our existing models or contact us for customized models today to meet your specific baling demands.



COCONUT FIBER BALER

SERIES 1 // SVB2-CF-1000. SVB2-CF-1200. SVB2-CF-1500. SVB2-CF-2000

CUSTOMIZED // MADE-TO-ORDER MODELS ARE AVAILABLE

FEATURES

Auto Chain Bale Ejector

efficiently pushes finished bales out of the compressing chamber

Multiple Door Opening Design Available

Front door & back door opening allows for higher number of straps to bind the bale

Right angle door enables the bale to eject faster and with minimal strain on the machine

Hydraulic-driven Door Opening

is optional for increasing work efficiency and cutting labor cost



Specifications

MODEL	SVB2-CF-1000	SVB2-CF-1200	SVB2-CF-1500	SVB2-CF-2000
Compressing force	100Tons	120Tons	150Tons	200Tons
Feed opening size (L * H)	1100*500mm	1100*500mm	1100*500mm	1100*500mm
Bale size	1100*700*(400-900) mm	1100*700*(400-900) mm	1100*700*(300-1000) mm	1100*700*(300-1000) mm
Compressing chamber size	1100*700*1400mm	1100*700*1400mm	1100*700*1500mm	1100*700*1500mm
Bale weight (approx.)	95-200kgs	100-230kgs	100-270kgs	110-300kgs
Voltage (customizable)	220-480V, 3phase, 50/60Hz	220-480V, 3phase, 50/60Hz	220-480V, 3phase, 50/60Hz	220-480V, 3phase, 50/60Hz
Power	15kw	15kw	18.5kw	22kw
Machine weight (approx.)	3300kgs	3800kgs	4500kgs	6000kgs
Overall dimension	1600*1000*3200mm	1600*1000*3450mm	1700*1100*3600mm	1700*1100*3700mm

* Unit bale weight depends on the material used and bale size you adjust